

STATELINE SPEEDWAY

V6 CLAIMER 2025 RULES

THIS CLASS HAS AN OPEN CLAIM FOR ANYONE IN THE GRANDSTANDS OR THE PITS FOR \$1500 + \$200 DEPOSIT THAT WILL BE RETURNED ONCE THE CLAIMED CAR ENTERS THE NEXT SCHEDULED EVENT FOR THIS CLASS.

- ANY front wheel drive V6 coupe, sedan, station wagon, or minivan. NO convertibles!
- NO all wheel drive or rear wheel drive allowed
- NO rotary, turbo, or supercharged engines
- ALL interior must be removed, except for the dash and drivers seat. ● ALL glass must be removed, except the front windshield (windshield can be replaced with LEXAN if removed)
- ALL exterior lights must be removed
- Cars must be neat appearing, NO BLACK CARS
- Car Numbers MUST be at least 18" tall and placed on BOTH doors and roof. Roof number must be read from the right side (passenger side) of the car. 6" number to be placed in the upper right (passenger) corner of the windshield - these are all required. NO triple digit numbers (777)
- May use stock hood release, but must have 12"x12" hole cut in hood for fire extinguisher access. If using hood pins, no fire extinguisher access hole is required.
- ALL engine components must be stock
- Fuel tank must be OEM and must remain in stock location
- Minimum 2" diameter with .125" wall thickness upright with 8"x8"x1/4" thick plates bolted to floor and roof. And 2" diameter with .125" wall thickness spreader bar going from left side to right side of car directly behind driver. Spreader bar and upright MUST be attached to each other.
- Battery may be relocated to inside the car & must be in a securely mounted and covered battery box; lid must have straps going both directions
- Racing seat belts REQUIRED & must be in good condition; Less than 4 years old and must have SFI date tag intact
- Window net REQUIRED and must be in good condition with SFI date tag attached - less than 4 years old
- Must have a minimum 6" channel at bumper height on driver's side - Must extend 6" into the front fender and 6" into the rear quarter panel. Must be held in place

with a minimum of SIX ½" diameter bolts with 2"x2" washers on both sides of the bolts. Ends of the channel must be smooth and at a 45 degree angle

- Minimum 2lb dry chemical fire extinguisher required. Must be within reach of driver and installed in a metal bracket. NO duct tape, bailing wire, zip ties or plastic brackets allowed. Must have gauge and needle must be in the green at all times.
 - Wheels to be of stock type steel or aluminum. No wider than 7". Tires must be no wider than a 225. Profile can be 60, 65, 70, or 75. Nothing softer than 400 treadwear
 - 6" minimum ride height at the lowest point of the car
 - All shocks/springs/coil overs must remain OEM or OEM replacement only. Heating or cutting of springs to get to ride height IS allowed. NO adjustable sway bars
 - Camber is allowed on front tires only and at 1" MAXIMUM
 - This class will be ran in various track directions - not just in a left hand circle. ●
- Refusing a claim will cause the car, driver AND number to be banned from the class for 1 calendar year

For questions or clarification, please contact:
Reesen Tarr - 509-863-7992