

# Stateline Speedway - Hobby Stock - Rulebook 2026

## **HOBBY STOCK**

Any American made rear wheel drive car 1955 through 2010. NO convertibles. NO fox body mustangs. NO two seaters. NO trucks. Ford to Ford, GM to GM, Mopar to Mopar, etc. Minimum wheelbase 101"

GEN 3 CAMARO MUST BE 54% LEFT

Racing Radios with ability to add RaceCeivers allowed. RaceCeivers are mandatory.

### **BODY:**

a. Aftermarket nose ok, must match model. Hoods, fenders, roof and q-panels MUST be OEM stock. Doors must be stock or 20-gauge steel. Hood, doors, and trunk lid may be gutted. If you have sheet metal quarter panels MUST be stock configuration and 20-gauge steel. Bumpers MUST be in stock configuration or covered. Stock firewall MUST be in place. All stock floorboards MUST be in place up to rear shock mounts, subject to 50 lb penalty if not met. Spoiler may be NO wider than 60 inches centered on trunk lid. Spoiler can be no wider than the body, NO OVERHANG and no taller than 6 inches MAX. Battery MUST be in a covered box with a master switch located behind driver. MUST have full windshield with clear Lexan. Wing windows no longer than 10-inches. 1. No Cold Air Box 2. Rear raised hood ok in center only for air cleaner clearance 3. 2.5" Hood Scoop "equal to factory" (A) ALL material under hood scoop from factory vents forward must be removed, purpose is to clear air cleaner. (B) Hood Scoops over 2.5" must be blocked off to only allow 2.5" opening 4. Can Not have raised rear of hood & hood scoop. One or the other 5. Hood Scoops with openings in front of air cleaner must be blocked off. Body MUST match chassis generation.

Bodies must remain stock appearing and in full spirit of class.

\*There must be an open space at the top of the windshield for the class sponsor.

### **ROLL CAGE:**

Fully conforming roll cages are required. Front hoops allowed. External driver's door nerf bar optional. All bars are subject to the Technical Director's approval. Roll bars are required and must be of at least one and one-half inches (1 1/2") O.D. steel pipe, one-eighth inch (1/8") wall thickness, one and three quarters (1 3/4") by ninety-five hundredths (.095) wall thickness on tubing. Roll bars MUST be welded or securely fastened inside the car to the floor pan and braced on the rear main bar. All roll bars have to have three (3) sissy bars on the driver's side connected with three (3) vertical bars in the center, with a minimum of two (2) sissy bars on the passenger side. All cars MUST have a rear safety bar attached to the main cage to protect the gas tank.

### **ENGINE HEADS:**

Approved stock production only. Bigger valves are ok and all seat work must be on the center line. Screw in studs ok. Rocker arms MUST be stock stamped steel. Rocker ratio MUST be stock per engine. NO porting, polishing, deburring, port matching. NO angle milling. NO stud girdle. NO oil deflectors. NO roller rockers. NO titanium retainers - "STEEL ONLY". NO titanium valves. NO epoxy. NO aluminum. NO welding. NO "N" heads. NO bowtie vortex. NO vortex. NO angle plug. NO W2. NO world SR. NO Ford Motorsports. NO aftermarket. NO Brzezinski (Stock dimension only).

### **CAMSHAFT:**

.530 lift MAX; Hydraulic cam. Hydraulic lifters MUST de-pump FULL stroke of lifter. NO hydraulic rollers. NO solid lifter cams. NO stacking of hydraulic lifters. NO gear drives.

### **BLOCKS:**

Stock OEM production only with part number. No Aluminum Blocks.

#### INTAKE MANIFOLD:

Stock OEM cast iron Q-Jet or low rise two barrel only. Two (2) big holes and two (2) small holes, low rise. Ford equivalent or subject to penalty. Dodge equivalent or subject to penalty. NO marine; Must have part number. No Aluminum except sealed GM 602 crates. No Brzezinski (stock dimension only)

#### EXHAUST MANIFOLD:

NO porting or port matching. NO headers. NO lighting. NO exit greater than two and one half (2 1/2). MUST have a muffler and pass at 95db. No Brzezinski (stock dimension only)

#### ROTATING:

Option 1: MUST be of stock weight and dimension. Flat tops only. Two (2) valve relief piston-OK. MAX cubic inch 360. Stroke MUST match block. NO stroked or de-stroked. NO light weight.

Option 2: See Weight

#### OIL SYSTEM:

NO dry sumps. NO external oil pumps. NO external oil filters.

#### RADIATOR:

Steel or aluminum; OK. NO antifreeze. MUST have a catch can. No electric water pump

#### CARBURETOR:

Holley 4412 five hundred (500) cfm 2 barrel with full choke horn. The part number MUST be on choke horn. Holley Replacement Parts only.

MUST pass complete BLP Gauges.

NO racing carburetors, VDL, Dorton, ETC . No Screw in Air Bleeds.

#### CARBURETOR SPACER PLATE:

One inch (1") carb spacer or Canton Phenolic. NO tapered, CNC milled or ANY high performance spacer.

#### AIR FILTER:

Fourteen inch (14") round, three inch (3") tall, MAX. K&N ok.

#### CLUTCH:

MUST be stock cast iron **or billet steel** flywheel; .870 thick or more. One (1) clutch disk. All steel pressure plate, ten and one-half inch (10 1/2") minimum. MUST have a one inch (1") access hole in bellhousing for visual on clutch and a one inch (1") hole in bell plate. NO racing clutches. MUST have scatter shield or belting. Clutch pedal and master cylinder can be aftermarket.

#### TRANSMISSION:

MUST have all forward gears and reverse. Automatic transmission MUST have torque converters, must have OEM part number.

#### REAREND:

Can be stock or nine-inch Ford (9"). Spool or welded only. NO limited slips. NO Detroit lockers. NO Gold Track. NO Gleason. NO traction enhancing differential. Spring shackles ok. Floaterers with drum brakes ok and are allowed, no cambered snouts. Any rear end with disc brakes, add 50 pounds. Must have stock OEM calipers only. **No aluminum 3rd members**

#### **DRIVELINE:**

MUST be steel; painted white. MUST have loop twelve inches (12") behind the transmission.

#### **BRAKES:**

MUST have ALL OEM brakes (4 working). Aftermarket brake pedal ok. Aftermarket master cylinder ok. Remote brake adjuster must be under dash OR hood - out of driver's reach. Stock calipers for make, model and generation only.

#### **WEIGHT:** Added weight must be painted white and clearly marked with your car #.

Must be mounted securely with minimum  $\frac{1}{2}$ " grade 5 bolts.

##### **Option 1:** Up to 360 cubic inch

Weight: 3200 min

Left: 55% max - 54% Gen 3 Camaro

Rear: 48% max

##### **Option 2:** Up to 400 cubic inch

Weight: 3400 min

Left: 55% max - 54% Gen 3 Camaro

Rear: 48% max

##### **Option 3:** GM Sealed 602 Crate with 6000 chip; MSD #8727CT soft touch HEI rev limiter on right side of dash out of reach of driver. No aftermarket seals.

Weight: 3225 min

Left 55% max - 54% Gen 3 Camaro

Rear 48% max

##### **Option 4:** GM 602 crate with aftermarket seals with 6000 chips; MSD #8727CT soft touch HEI rev limiter on right side of dash or firewall out of reach of driver (authorized rebuilt by TRE only)

Weight: 3275 min

Left 55% max - 54% Gen 3 Camaro

Rear 48% max

#### **SHOCKS:**

Steel Body Non-Adjustable-Non Rebuildable-Mounted in Stock Location using Stock Mounting Hardware. **No Screw on ends.** \$150 Claim Per Shock. Claim must be made by a Hobby DRIVER competing in that evening. Claim must be in cash and in writing and

presented to the Tech Director between Qualifying and 15 minutes before the Hobby main event. If you refuse the claim you will lose all money and points for the night.

**RIDE HEIGHT:**

- a. 5-inch ride height from lowest part of frame at driver's door.
- b. Nose and skirts 5-inch.

**A-ARMS:**

Stock OEM only

**Tie Rods:**

Must be stock OEM. No Heims.

**SPINDLE:**

MUST be stock OEM

**HUB:**

Must be stock OEM. No 2 piece racing hubs

**CAMBER:**

Two inch (2") right and one inch (1") left max measured with square at top of wheel.

**WEIGHT JACKS:**

NO weight jacks. Pocket spring adjusters ok.

**TRAILING ARM:**

MUST be stock OEM dimension. MUST be in stock location. NO alteration allowed. Steel or Poly Leaf springs - OK

**SWAY BAR:**

One and one quarter inch (1 1/4") max in stock OEM saddles. All thread ok for adjustment. NO Heims. No At Frame Adjusters.

**IGNITION:** NO MSD IGNITION BOXES IN ANY COMBO

Option 1: Firing order MUST be stock per engine. NO crank triggers. NO electronic tuning.

Option 2: 4-7 swap okay.

Option 3: 602 - MSD#8727CT soft touch rev limiter

**FUEL CELL:**

MUST be covered in twenty (20) gauge steel in trunk location. Fuel filter MUST be metal. Fuel line MUST be in conduit if located through car. Fuel cell no lower than ten inches (10") and no closer than twelve inches (12") from back bumper.

**FUEL PUMP:**

**Mechanical only. NO electric. Oberg type anti siphon shut off valve mandatory.**

**FUEL:**

**No oxygenated fuel, NO CHP, CHP Plus, C-85 or E85.**

**WHEELS:**

**15 x 7 or 15 x 8 steel racing wheel. 5/8 wheel stud mandatory.**

**TIRES:**

**Hoosier 970. NO softening inside or outside. NO poking. NO tire shine. The tire you qualify with you MUST start the main event with. Qualifying tires will be stamped at the scales prior to qualifying.**

**SAFETY:**

**MUST have race padding on all bars that your hands and head can reach. MUST have a window net. MUST have three inch (3") wide shoulder belt. ALL belts must be five (5) years or newer. MUST have two inch (2") sub belt. MUST have fire extinguisher. MUST have master electrical shut off behind driver's seat. Helmet **MUST** be SNELL SA **2015** or newer; NO motorcycle helmets. Head and neck restraint recommended. Driver's suit must be clean with no visible holes. Racing gloves must be worn at all times. Holes around shifter must be covered. Seats must be aluminum. 2" belt okay with HANS or Youth.**

**TRANSPONDER:**

**Location: Right rear frame rail; fifteen inches (15") behind center of rear end.**

**CAR NUMBERS:**

**Doors: Twenty-four inch (24") MINIMUM**

**Roof: Thirty inch (30") MINIMUM**

**\*These rules can be adjusted anytime to even competition.**